

# FICHA TÉCNICA

**WELDWELL®**  
**KOBE**  
LASMAQUINASDESOLDAR

**WelderPower®**  
Premium Welding Products.

● TRABAJO  
LIVIANO

● TRABAJO  
SEMI-PESADO

● TRABAJO  
PESADO

**WELDWELL®**



**WELDWELL®**  
**PC-150 KOBE**

|                               |            |
|-------------------------------|------------|
| POWER SUPPLY                  | 220V ± 15% |
| FREQUENCY                     | 50 - 60HZ  |
| PHASE                         | 3PH        |
| RATED INPUT (KVA)             | 26         |
| OPEN CIRCUIT VOLTAGE(V)       | 330        |
| AMPERAGE RANGE(A)             | 40-150     |
| RATED DUTY CYCLE (31C°)       | 80%        |
| RATED WORKING VOLTAGE(V)      | 96-140     |
| EFFICIENCY                    | 0.85       |
| POWER FACTOR                  | 0.93       |
| MAX CUTTING THICKNESS (MM)    | 45         |
| QUALITY CUTTING THICKNESS(MM) | 30         |
| COMPRESSED AIR PRESSURE (PSI) | 40 - 80    |
| POST FLOW TIME(KG)            | 0 - 5      |
| DIMENSIÓN (L X W X H)(CM)     | 65*36*53   |
| NET WEIGHT (KGS)              | 49         |



## ● ACCESORIOS INCLUIDOS



Guantes  
de soldar.



Tierra con  
cable.



Antorcha  
PLASMA



Filtro de aire

## ● ACCESORIOS QUE NO INCLUYEN



Compresor  
de aire



Mascara  
de cortar

